

## **FGOC ECPlus<sup>+</sup> MILLED FIBERS**

FGOC ECPlus<sup>+</sup> Milled Fibers are produced by milling of boron free E-glass fiber strands, to the desired length.

ECPlus<sup>+</sup> Milled Fibers are specifically designed for the reinforcement of Thermoset - and Thermoplastic resins and as anticrack in coating & gel-coating applications and can be coated to improve mechanical properties.

ECPlus<sup>+</sup> Milled Fibers offer excellent process-ability and flow properties, as well as compatibility with the specific resin, impregnation and dispersion characteristics.

## PRODUCT FEATURES

Product	Glass Type	Application	Moisture (%) ISO 3344	<b>Lol (%)</b> ISO 1887	Filament Diameter (µm) ISO 1888	Length (µm)
ECPlus⁺ Milled Fibers	Boron free 'E' Glass	Polyester, Vinylester Epoxy Multi (UP, PBT, PET, PC) Polyamide 6.6 Polypropylene Acrylic Concrete	<0.1	0.6-0.9 0.6-0.9 0.6-1.0 0.5-0.9 0.8-1.2 0.6-0.9 0.5-0.8	10 12 14 16	50 150 190 210

Other specifications are available on request.

## PACKAGING

Packaging	Pallet size	Net weight
Big Bag	1140x1140x1160mm	~ 600 – 1000 kg
Bags (25kgs) 36 bags per pallet	1140811408110011111	~ 900 kg

## STORAGE

The product should be stored in a cool and dry area, with temperatures between 15°C and 35°C and relative humidity below 75%. It is advisable to condition it in the workshop for at least 24 hours before use. Pallets should not be stacked more than 2 layers high.

The information and data contained in this document is offered solely as a guide in the selection of a product. The information is based on actual laboratory data and field tests experience. FGOC believe this information to be reliable, but do not guarantee it's applicability to the user's process or assume any responsibility or liability arising out of it's use and/or performance. The user agrees to be responsible for thoroughly testing any application to determine it's suitability before using the product. FGOC reserves the right to update and modify specifications without prior noticed. Because of numerous factors affecting results, FGOC makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for aparticular purpose.

FIBER GLASS OASIS COMPANY :





Web : www.fgoc.com.sa

Fax: +966 14 328 9596.



